



A Heytex group company

STYLE: C10641
DragonTuf
Vinyl Laminated Polyester

TYPICAL PERFORMANCE PROPERTIES

Total Weight

ASTM D-751 10 oz. / yd.²

Grab Tensile

ASTM D-751 130 x 150 lbs.

Strip Tensile

ASTM D-751 70 x 80 lbs. / in.
Procedure B

Tongue Tear

ASTM D-751 35 x 40 lbs.
8x10 Specimen @ 12 in. / min.

Trap Tear

ASTM D-751 25 x 35 lbs.

Adhesion

ASTM D-751 20 lbs. / in.
RF Weld

Low Temperature

ASTM D-2136 -40 ° F

Flame Resistance

Cal. Fire Marshal-Title 19 Pass
NFPA 701 Pass
FAR 25.853 (a) Pass

Date Issued: September 6, 2010

We believe this information is the best currently available, but assume no obligation or liability in connection therewith. We make no guarantee of results and no representation that the material is fit for any particular purpose. There are NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY, unless specified in writing and signed by BondCote Corporation

P: 540.980.4461 | 800.255.9338 | F: 540.980.4466
P.O. Box 729, 509 Burgis Avenue, Pulaski, VA 24301
www.bondcote.com ISO 9001: 2008 Certified