



A Heytex group company

**C85-641**  
**Commercial Tent Flooring**  
**Vinyl, Polyester, Laminate**

PERFORMANCE METHODS	STANDARD	METRIC
<u>Total Weight</u> ASTM D 751	8.5 oz. / sq. yd.	288 g/m <sup>2</sup>
<u>Grab Tensile</u> ASTM D 751	130 x 150 lbs.	578 x 667 N
<u>Strip Tensile</u> ASTM D 751 Procedure B	70 x 80 lbs.	311 x 355 N
<u>Tongue Tear</u> ASTM D 751 8 X 10 Specimen @12in. / min.	35 x 40 lbs.	155 x 177 N
<u>Trap Tear</u> ASTM D 751	25 x 35 lbs.	111 x 155 N.
<u>Adhesion</u> ASTM D 751, lbs /2 inch Dielectric Weld, (RF)	20 lbs / in.	89 N / 5 cm
<u>Flame Resistance</u>  Cal. Fire Marshal - Title 19 FAR 25.853 (b)	Pass Pass Pass	Pass Pass Pass
<u>Low Temperature</u> ASTM D 2136 @ - 40 Degrees F.	Pass	Pass

We believe this information is the best currently available, but assume no obligation or liability in connection therewith. We make no guarantee of results and no representation that the material is fit for any particular purpose. There are NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY, unless specified in writing and signed by BondCote Corporation

P: 540.980.4461 | 800.255.9338 | F: 540.980.4466  
P.O. Box 729, 509 Burgis Avenue, Pulaski, VA 24301  
www.bondcote.com ISO 9001: 2008 Certified