



A Heytex group company

**STYLE: G35415**  
**Standard Dock Seal**  
**Vinyl Coated Polyester**

**TYPICAL PERFORMANCE PROPERTIES**

Total Weight

ASTM D-751 35 oz. / yd.<sup>2</sup>

Grab Tensile

ASTM D-751 510 x 470 lbs.

Strip Tensile

ASTM D-751 305 x 285 lbs. / in.  
Procedure B

Tongue Tear

ASTM D-751 125 x 125 lbs.  
8x10 Specimen @ 12 in. / min.

Adhesion

ASTM D-751 10 lbs. / in.+  
RF Weld

Puncture Resistance

ASTM D-4833 255 lbs.

Hydrostatic Resistance

ASTM D-751 680 psi  
Procedure A

Low Temperature

ASTM D-2136 - 40° F

Abrasion Resistance

ASTM D-3384 10,000 cycles  
H22, 1000 gram load

Mildew Resistance

ASTM G-21 No Growth

Date Issued: September 6, 2010

We believe this information is the best currently available, but assume no obligation or liability in connection therewith. We make no guarantee of results and no representation that the material is fit for any particular purpose. There are NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY, unless specified in writing and signed by BondCote Corporation

P: 540.980.4461 | 800.255.9338 | F: 540.980.4466  
P.O. Box 729, 509 Burgis Avenue, Pulaski, VA 24301  
www.bondcote.com ISO 9001: 2008 Certified